



SOUTHERN IONICS MINERALS, LLC (SIM)
SAFETY DATA SHEET

SDS NO. 006
 Effective Date: 12/01/2015
 Revision Date: 09/23/2016

I. Product and Company Information

SII Product Name(s):	Leucoxene Sand	Synonym:	Georgia Leucoxene Altered Ilmenite
Chemical Name:	Iron Titanium Oxide	CAS Number:	12173-81-8
Manufacturer's Name: Southern Ionics Minerals, LLC 13291 Vantage Way, Suite 103 Jacksonville, FL 32218 Web Site www.simineralsllc.com		Emergency Contacts: For Emergency Incident Information Call CHEMTREC at 1-800-424-9300 CHEMTREC CCN - 20596	

II. Hazard Identification

OSHA HCS / GHS Classification(s):		Hazard Statement(s):	
NOT CLASSIFIED AS HAZARDOUS		No known significant effects or critical hazards	
Signal Word:	Precautionary Statement(s):		
No signal word			
Symbol(s): No symbol	Prevention:	Not applicable	
	Response:	Not applicable	
Additional Label Information:		Leucoxene sand contains a small amount of free quartz (up to 0.5%) and precautions should be taken to avoid inhaling the dust. The normal grain size of the product precludes it from being an inhalation hazard.	
Hazards Not Otherwise Classified:		Handling and/or processing of this material may generate dust which can cause mechanical irritation of the eyes, skin, nose and throat.	

III. Composition / Information on Ingredients

Chemical Name:	CAS Reg #'s	%
Rutile/Leucoxene	12173-81-8	93 – 97 %
Ilmenite	103170-28-1	< 97 %
Zircon	14940-68-2	0.1 – 0.5 %
Monazite	1306-41-8	0.2 – 0.3 %
Staurolite	12182-56-8	< 1%
Quartz	14808-60-7	Up to 0.5 %

Comments:	Respirable Crystalline Silica < 0.01%
------------------	---------------------------------------

IV. First Aid Measures

Eyes:	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Remove any contact lenses. If eye irritation persists get medical advice/attention.
Dermal / Skin:	Remove contaminated clothing to avoid generating dust. Wash material from the skin. If repeated contact results in skin irritation, get medical advice/attention. Launder clothing before reuse.
Inhalation:	Move to fresh air immediately. Blow nose to remove particles from nasal passages. If any adverse reaction develops, seek medical attention.
Ingestion:	There are no known hazards resulting from accidental ingestion of Leucoxene Sand as may occur during normal handling. Consult a physician if necessary.

V. Fire Fighting Measures

NFPA Hazard Rating:	Health (Blue)	Fire (Red)	Reactivity (Yellow)	Special Instructions (White)
	1	0	0	
NFPA Hazard Classification: 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme				
Extinguishing Media:	Product does not burn. Use extinguishing media suitable for the surrounding fire.			
Special Firefighting Procedure:	No fire or explosion hazard exists.			
Specific hazards arising from the chemical:	Use firefighting methods appropriate to local circumstances and the surrounding environment.			

VI. Accidental Release Measures



Precaution if Spilled or Released:	Use personal protective equipment recommended in SECTION 8 during clean-up. Avoid generating dust. Absorb, sweep up, and place in container for re-use or disposal.
Neutralizing Chemicals:	Reduce dust spreading with a water spray.
Environmental Precautions:	Prevent product from entering drains and waterways.

VII. Handling and Storage

Handling:	Avoid contact with eyes. Avoid creating dust in handling, transfer or clean-up. Avoid breathing dust. Use only with adequate ventilation. Wash thoroughly after handling.
Storage:	This material is not hazardous under normal storage conditions; however, material should be stored in closed containers, in a secure area to prevent container damage and subsequent spillage.

VIII. Exposure Control / Personal Protective Equipment

Component Workplace Control Parameters:				
Components:	CAS-No.	Value	Parameters	Basis
Silica, Crystalline Quartz	14808-60-7	TLV	0.1 mg/m ³	ACGIH (respirable fraction)
Titanium Dioxide	13463-67-7	TLV	10 mg/m ³	ACGIH (total dust)
Zirconium Silicate	14940-68-2	TLV	5 mg/m ³	ACGIH (as Zr)
Engineering Controls:	Use engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to keep exposures below their respective threshold limit value. If practical, use local mechanical exhaust ventilation at sources of air contamination, such as open process equipment.			
General Hygiene:	Practice good personal hygiene after using this material, especially before eating, drinking, smoking, or using the toilet.			
Personal Protection Equipment:				

Eye:		Wear safety glasses with side shields in normal conditions. Wear dust-proof goggles in dusty conditions.			
Skin:		Wear clothing sufficient to cover the skin, safety shoes, and impervious gloves for hand protection against dry material.			
Respiratory:		Use NIOSH/MSHA approved respiratory protection (air purifying or air supplying) with a type 100 (high efficiency particulate cartridge or canister) where concentrations are above airborne exposure limits.			
Radiation Exposure:		Occupational exposure should be as low as reasonably achievable, (ALARA principle), but should not exceed a total of 100 milli-seiverts over five consecutive years, (ICRP).			
HMIS Classification:	Health (Blue)	Flammability (Red)	Physical Hazard (Yellow)	PPE (White)	
	1	0	0	See Above	
Hazard Classification: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe					

IX. Physical and Chemical Properties

Physical State:	Solid	pH:	Neutral
Appearance:	Dark brown to black free running sand	Odor Threshold:	NA
Odor:	Odorless	Vapor Pressure:	NA
Specific Gravity:(H₂O=1)	4.0 - 4.2	Melting Point:	1800°C
Vapor Density: (Air=1)	NA	Upper Explosive Limit:	NA
Boiling Point:	NA	Autoignition Temp:	NA
Lower Explosive Limit:	NA	Bulk Density:	2000 to 2400 kg/m ³
Flash Point:	NA	Grain Size (AFS No)	75 - 90
Solubility in water:	Insoluble	Other:	

X. Stability and Reactivity Data

Reactivity	This material is considered inert.
Chemical Stability:	Stable at normal conditions.
Conditions To Avoid:	None known.
Incompatible Materials:	None in normal or expected use.
Hazardous products of Decomposition:	None under normal use.

XI. Toxicological Information

Routes of Entry:	<input checked="" type="checkbox"/> Eyes <input checked="" type="checkbox"/> Skin <input checked="" type="checkbox"/> Ingestion <input checked="" type="checkbox"/> Inhalation					
Sign and symptoms of Exposure:	May cause irritation to eyes, skin, and respiratory passages.					
Eye Contact:	Contact may result in mechanical (abrasive) irritation.					
Ingestion:	No adverse effects expected for incidental ingestion.					
Skin Contact:	Contact may result in mechanical (abrasive) irritation.					
Inhalation:	<p>Leucoxene sand contains a small amount of respirable crystalline silica (up to 0.01%) and precautions should be taken to avoid inhaling the dust. The normal grain size of the product precludes it from being an inhalation hazard.</p> <p>Leucoxene sand contains low levels of naturally occurring radioactive elements of the uranium and thorium series. It has typical specific activities of 0.15 to 1.1 Bq/g (thorium-232) and 0.2 to 0.75 Bq/g (uranium-238). Low level gamma radiation from bulk or bagged stockpiles of Leucoxene sand can increase gamma levels slightly above normal background.</p>					
Carcinogenicity:						
Respirable Crystalline Silica (Quartz)	NTP	Known	IARC	Group 1	OSHA	

Ingredient Name:	Species	Test	Route	Results
Crystalline Silica (Quartz)	Rat	>11,000 mg/kg	Oral	ALD
Crystalline Silica (Quartz)	Carp	>10,000 mg/L	Aquatic	LC 50
Rutile	Mice	>200 mg/kg	Oral	LD 50
Titanium Dioxide	Rat	>10,000 mg/kg	Oral	LD 50
Comments:				

XII. Ecological Information

Ingredient Name:	Species	Test	Period	Results
Comments:	This product is not anticipated to cause adverse effects to animal or plant life if released to the environment in small quantities. The material is unlikely to cause any environmental damage. It is insoluble in water and is unlikely to contaminate waterways or food chains.			

XIII. Disposal Considerations

Waste Disposal:	Recover, reclaim or recycle when practical. Disposal must be in accordance with federal, state, and local regulations. If approved, may be transferred to an approved landfill site. Consult and comply with current regulations regarding disposal of waste containing NORMs above background levels.
------------------------	--

XIV. Transportation Information

Proper Shipping Name:	None allocated				
DOT Classification:	Not regulated by U.S. DOT as a hazardous material				
Identification Number:	NA	Packing Group:	NA	Other Labels:	NA
Comments:	This product is not classified as "dangerous goods" under IAEA SSR 6, IMDG, IATA, Transport Canada and EU transport regulations.				

XV. Regulatory Information Based on Largest Component (unless listed)

TSCA Status	Yes	SARA 302 TPQ	Not Listed
		SARA 304 RQ	Not Listed
		SARA 313 List	Not Listed
		CERCLA (RQ)	Not Listed
		SARA 311/312	<input type="checkbox"/> Acute <input checked="" type="checkbox"/> Chronic <input type="checkbox"/> Fire <input type="checkbox"/> Release of Pressure <input type="checkbox"/> Reactive
International Regulations:			Other Regulations:
			California PROP 65 (Quartz) Known Carcinogen

XVI. Other Information

NSF Certification:	
Other:	_____
Revision Notes:	_____
MSDS Replacements:	<u>SIM MSDS Leucoxene Sand Products</u>

SALES OFFICE

13291 Vantage Way, Suite 103 Jacksonville, FL 32218
TEL: 904-741-0090

For Product Information:

TEL: 912-647-0301
FAX: 904-741-0091

IMPORTANT

Although the information contained is offered in good faith, SUCH INFORMATION IS EXPRESSLY GIVEN WITHOUT ANY WARRANTY (EXPRESS OR IMPLIED) OR ANY GUARANTEE OF ITS ACCURACY OR SUFFICIENCY and is taken at the user's sole risk. User is solely responsible for determining the suitability of use in each particular situation. SIM specifically DISCLAIMS ANY LIABILITY WHATSOEVER FOR THE USE OF SUCH INFORMATION, including without limitation any recommendation which user may construe and attempt to apply which may infringe or violate valid patents, licenses, and/or copyright.